

**CONFIDENTIAL: IF RECEIVED BY A PARTY OTHER THAN THE NAMED
ADDRESSEE, SEE THE CONFIDENTIALITY NOTICE BELOW!**

RATNER & PRESTIA
Suite 301
One Westlakes, Berwyn
P.O. Box 980
Valley Forge, PA 19482-0980
Phone: (610) 407-0700
Fax: (610) 407-0701

FACSIMILE COVER SHEET

DATE: June 6, 2002OUR REF NO.: MAT-7938US

TIME: _____

SERIAL NO.: 09/509,928

FROM:	Lawrence E. Ashery
TO:	Examiner Richard Lee
COMPANY:	USPTO
FAX TELEPHONE:	(703) 746-4147
OFFICE TELEPHONE:	
TITLE OF DOCUMENT:	PENDING CLAIMS

TOTAL NUMBER OF PAGES: 10 (including this form)COMMENTS: As we discussed, the restriction requirement. Please call me after you have reviewed the attached pending claims.

*** CONFIDENTIALITY NOTICE**

This facsimile transmission (and/or documents accompanying it) may contain Confidential Information belonging to the sender which is protected by the Attorney-Client privilege. The information is intended only for the use of the individual or entity named above. If you are not the intended recipient, you are hereby notified that any disclosure, copying, distribution or the taking of any action in reliance on the contents of this information is strictly prohibited. If you have received this transmission in error, please immediately notify us by telephone to arrange for return of the documents.

Please notify us immediately if you have not received the number of pages indicated above.

PENDING CLAIMS

- 1 1. A low-resistance resistor comprising:
2 a resistor element made of a metal sheet; and
3 a metal terminal disposed at both ends of said resistor element,
4 said terminal has an electrical conductivity equal to or greater
5 than that of said resistor element, and
6 said terminal has a groove of a width fittable to said resistor
7 element, and;
8 said resistor element and said terminal are electrically connected
9 by inserting said resistor element into said groove with a third metal inbetween.
1 2. The low-resistance resistor as defined in Claim 1, wherein a
2 thickness of said terminal is thicker than a total thickness of said resistor
3 element.
1 4. The low-resistance resistor as defined in Claim 1, wherein at
2 least a part of a surface of said resistor element is covered with an insulating
3 layer.
1 5. The low-resistance resistor as defined in Claim 4, wherein said
2 insulating layer completely covers said resistor element.
1 6. The low-resistance resistor as defined in Claim 4, wherein said
2 insulating layer is made of at least one of epoxy resin, polyimide resin, and
3 poly-carbodiimide resin.
1 7. A low-resistance resistor comprising:
2 a resistor element made of metal sheet;
3 an insulating substrate disposed at least on one of top and bottom
4 faces of said resistor element;

5 a terminal having a groove of a width equivalent to a sum of a
6 thickness of said resistor element and said insulating substrate; and

7 a third metal formed between said resistor element and said
8 groove;

9 wherein said resistor element and said terminal are electrically
10 connected through said third metal.

1 8. The low-resistance resistor as defined in Claim 7, wherein said
2 insulating substrate is made of one of alumina, glass, glass impregnated epoxy
3 resin substrates, and paper impregnated phenolic resin substrates.

1 9. The low-resistance resistor as defined in Claim 7,

2 wherein an insulating layer covers a part of a surface of said
3 resistor element.

1 10. The low-resistance resistor as defined in Claim 7, wherein a
2 thickness of said terminal is at least three times of a sum of a thickness of said
3 resistor element and a thickness of said insulating substrate.

1 11. A low-resistance resistor comprising:

2 a resistor element made of metal sheet; and

3 a metal terminal disposed at both ends of said resistor element,
4 said terminal being made of metal having greater electrical conductivity than
5 that of said resistor element, and having an L shape section face;

6 wherein said resistor element and said terminal are electrically
7 connected through a third metal.

1 12. The low-resistance resistor as defined in Claim 11, wherein
2 at least a part of a surface of said resistor element is covered with an insulating
3 layer.

1 13. A low-resistance resistor comprising:

2 a resistor element made of metal sheet:

3 an insulating sheet attached to at least one face of said resistor
4 element; and

5 a metal terminal disposed at both ends of said resistor element,
6 said terminal being made of metal having greater electrical conductivity than
7 that of said resistor element, and having an L shape section face;

8 wherein said resistor element and said terminal are electrically
9 connected through a third metal.

1 14. A resistor comprising:

2 a metal resistor element provided with a step between both ends
3 by making a thickness of said both ends thicker than a central portion; and

4 a metal terminal disposed at both ends of said resistor element,
5 said terminal having a one-side-open section face with an inner space broader
6 than its opening, and being electrically connected to said step of said resistor
7 element at least at said inner space of the opening.

1 15. A low-resistance resistor comprising:

2 a resistor element made of metal sheet;

3 an insulating substrate; and

4 at least two metal terminals formed in a way to electrically
5 connect top and bottom faces of said insulating substrate;

6 wherein said resistor element and said metal terminals are
7 electrically connected through a third metal.

1 16. The low-resistance resistor as defined in Claim 15, wherein
2 at least a part of a surface of said resistor element is covered with an insulating
3 layer.

1 17. The low-resistance resistor as defined in Claim 15, wherein
2 said insulating substrate is made of one of alumina, glass, glass impregnated
3 epoxy resin substrates, and paper impregnated phenolic resin substrates.

1 18. A low-resistance resistor comprising:

2 a resistor element made of metal sheet; and

3 four metal terminals, said terminals being disposed one each on
4 top and bottom faces at both ends of said resistor element, and electrically
5 connected to said resistor element through third metal.

1 19. The resistor as defined in Claim 18, wherein a width of said
2 terminals are not less than a width of said resistor element.

1 20. The resistor element as defined in Claim 18, wherein said
2 terminals disposed on top and bottom faces at both ends of said resistor element
3 are electrically connected to each other.

1 21. A resistor comprising:

2 a metal resistor element having a notch near both ends; and

3 a metal terminal disposed at both ends of said resistor element,
4 said terminal having a protrusion corresponding to said notch;

5 wherein said resistor element and said terminal are electrically
6 connected at least through said protrusion and said notch.

1 22. A resistor comprising:

2 a metal resistor element having at least two through holes; and

3 a metal terminal having at least one protrusion with a same shape
4 as said through holes;

5 wherein at least one protrusion of said terminal is inserted to at
6 least one through hole of said resistor element, and at least one face of said

7 terminal is electrically connected to said resistor element.

1 23. The low-resistance resistor as defined in Claim 18, wherein
2 at least a part of a surface of said resistor element is covered with an insulating
3 layer.

1 24. The low-resistance resistor as defined in Claim 21, wherein
2 at least a part of a surface of said resistor element is covered with an insulating
3 layer.

1 25. The low-resistance resistor as defined in Claim 22, wherein
2 at least a part of a surface of said resistor element is covered with an insulating
3 layer.

1 28. A method for manufacturing a low-resistance resistor
2 comprising:

3 forming a resistor element made of a metal sheet, said resistor
4 element having a shape adjusted to obtain a predetermined resistance;

5 forming a metal terminal having a groove;

6 fitting said terminal to both ends of said resistor element; and

7 electrically connecting said resistor element and said terminal;

8 wherein a third metal layer is formed on at least one of

9 a) a connecting portion of said resistor element, and

10 b) connecting portion of said terminal

11 before fitting said terminal to said resistor element.

1 29. The method for manufacturing a low-resistance resistor as
2 defined in Claim 28, further comprising the step of forming an insulating layer
3 except on said terminal after said step of electrical connection.

1 30. A method for manufacturing a resistor comprising:

2 forming a terminal made of a metal foil pattern with a
3 predetermined shape on a part of top and bottom faces of an insulating
4 substrate, said terminal being electrically connected to top, side, and bottom
5 faces of said insulating substrate;

6 dividing said insulating substrate into a predetermined shape;

7 forming a metal resistor element, said resistor element having a
8 shape adjusted to obtain a predetermined resistance;

9 electrically connecting said resistor element to the metal foil
10 pattern on the top face of said insulating substrate.

1 31. A method for manufacturing a resistor comprising:

2 forming a metal resistor element, said resistor element being
3 adjusted to obtain a predetermined resistance;

4 forming a block of metal terminal having at least one protrusion;

5 creating at least two through holes at a predetermined position of
6 said resistor element;

7 inserting at least one of said protrusion into at least one of said
8 through hole;

9 folding an open side of said terminal to hold said resistor in a
10 thickness direction; and

11 electrically connecting said resistor element and said terminal.

1 32. The method for manufacturing a low-resistance resistor as
2 defined in Claim 28, wherein said terminal is electrically connected to both
3 ends of said resistor element by one of pressing, caulking, and cold forging, and
4 then one of heating, thermal compression bonding, brazing, and ultrasonic
5 welding.

1 33. The method for manufacturing a low-resistance resistor as
2 defined in Claim 28, wherein said step of forming said third metal layer is
3 implemented by one of plating and paste printing.

1 34. The method for manufacturing a resistor as defined Claim
2 28, wherein said step of electrically connecting said resistor element and
3 terminal comprises :

4 coating said at least one of said resistor element and terminal with
5 metal different from that used for forming said resistor element and said
6 terminal;

7 connecting said resistor element and said terminal, after
8 assembling coated resistor element and terminal, by one of brazing, pressing,
9 and ultrasonic welding.

1 35. A method for manufacturing a resistor comprising:

2 forming a metal resistor element, said resistor element having a
3 shape adjusted to obtain a predetermined resistance;

4 forming one of a notch and groove at a predetermined position of
5 said resistor element;

6 forming a block of metal terminal with a predetermined shape,
7 said terminal having at least one protrusion;

8 sandwiching said resistor element with said terminal, and
9 inserting said protrusion into one of said notch and groove; and

10 electrically connecting said resistor element and said terminal.

1 36. A method for manufacturing a resistor comprising:

2 forming a resistor element made of metal sheet, said resistor
3 element having a shape adjusted to obtain a predetermined resistance; and
4 having one of at least two through holes, notches, grooves, and cavities;

5 forming a terminal made of metal strip, said terminal being one of
6 sandwiched and folded on top, bottom, and side faces at both ends of said
7 resistor element, and a part of metal being inserted and fixed to one of said
8 through holes, notches, grooves, and cavities of said resistor element; and

9 electrically connecting said resistor element and said terminal.

1 37. The method for manufacturing a low-resistance resistor as
2 defined in Claim 29, wherein a step of trimming resistance is added before said
3 step of forming said insulating layer.

1 44. The low-resistance resistor as defined in Claim 2, wherein a
2 thickness of said terminal is at least three times of a total thickness of said
3 resistor element.

1 45. The method for manufacturing a low-resistance resistor as
2 defined in Claim 29, wherein said terminal is electrically connected to both
3 ends of said resistor element by one of pressing, caulking, and cold forging, and
4 then one of heating, thermal compression bonding, brazing, and ultrasonic
5 welding.

1 46. The method for manufacturing a low-resistance resistor as
2 defined in Claim 30, wherein said terminal is electrically connected to both
3 ends of said resistor element by one of pressing, caulking, and cold forging, and
4 then one of heating, thermal compression bonding, brazing, and ultrasonic
5 welding.

1 47. The method for manufacturing a low-resistance resistor as
2 defined in Claim 31, wherein said terminal is electrically connected to both
3 ends of said resistor element by one of pressing, caulking, and cold forging, and
4 then one of heating, thermal compression bonding, brazing, and ultrasonic
5 welding.

1 48. The method for manufacturing a resistor as defined in Claim
2 29, wherein said step of electrically connecting said resistor element and
3 terminal comprises :

4 coating said at least one of said resistor element and terminal with

5 metal different from that used for forming said resistor element and said
6 terminal;

7 connecting said resistor element and said terminal, after
8 assembling coated resistor element and terminal, by one of brazing, pressing,
9 and ultrasonic welding.

1 49. The method for manufacturing a resistor as defined in Claim
2 30, wherein said step of electrically connecting said resistor element and
3 terminal comprises :

4 coating said at least one of said resistor element and terminal with
5 metal different from that used for forming said resistor element and said
6 terminal;

7 connecting said resistor element and said terminal, after
8 assembling coated resistor element and terminal, by one of brazing, pressing,
9 and ultrasonic welding.

1 50. The method for manufacturing a resistor as defined in Claim
2 31, wherein said step of electrically connecting said resistor element and
3 terminal comprises :

4 coating said at least one of said resistor element and terminal with
5 metal different from that used for forming said resistor element and said
6 terminal;

7 connecting said resistor element and said terminal, after
8 assembling coated resistor element and terminal, by one of brazing, pressing,
9 and ultrasonic welding.